

DISTRIBUTORS OF LEATHER, VINYL, FABRIC & FOAM 4527 GLENWOOD ROAD • BROOKLYN, NY 11203

Phone: 718 941 3326 • Fax: 718 941 6115

Email: mark@dvcfabric.com

WOVEN HUES



WOVEN HUES with



is manufactured to meet the following typical properties:

Width	
Roll Size	30 yds.
Nominal Weight	30 oz. per Lin. yard
Contents	
Cold Crack	-10°F
UV Stabilized Pigments	300 hours minimum
Abrasion Resistance	Wyzenbeek (100,000 cycles #10 cotton duck)
Class Ratings	ASTM D 3690 - Class A
Thickness	1.05 mm
Mildew Resistant	Front and Back
Anti-Bacterial/Anti-Microbial (AATCC 147 / ASTM G-	21) Pass

Suggested Applications:

Conference Room, Executive Seating, Office, Residential, Hospitality, Lounge Seating, Healthcare, Restaurant Seating

Meets flammability requirements*:

Motor Vehicle Safety Standard 302 California Technical Bulletin 117-2013, Section 1 NFPA 260 Class 1 UFAC Class 1 BIFMA Class A This product has been treated with anti-bacterial and anti-microbial agents that will provide resistance to the following:

(AATCC Test Method 147)

Bacillus Mycoides Straphylococcus Aureus Klebsiella Pneumoniae Salmonella Choleraesuis

STAINING AGENT

X

KETCHUP &

х

X

LIPSTICK

х

BLUE JEAN

х

х

Proteus Vugaris Bacillus Cerus
Enterococcus Faecalis Escherichia Coli

PEN MARKS

х

X

FORBID_a dramatically increases the stain resistance, while preserving the integrity of the fabric luster and softness.

FORBID Cleaning instructions:

Method One: For most common stains and spills,

use mild soap and water.

Method Two: If Method One doesn't work,

use the following household items - FANTASTIK • 409 • MR. CLEAN.

Method Three: For tougher stains such as sharpie, paint and lipstick, use a 70% isopropyl alcohol wipe.

For more information, please visit www.forbidsrt.com

The EnduratexTM care guide addresses the performance of FORBID products as indicated in product testing, conducted under laboratory conditions. Results may vary under actual conditions. The information contained in the care guide is not a guarantee and does not relieve the user of the responsibility of proper and safe use of the product and the use of recommended cleaning

agents. The use of certain agents has been found to be harmful to the surface appearance and lifespan of viryl, please familiarize yourself with those substrates for best results.

EnduratexTM topcoat, FORBID, is resistant to most common stains; however, existing dyes and pigments in some staining agents have been seen to create a permanent stain if not properly

EnduratexTM maintains the highest viryl production standards. Anomalies may occur during finishing if the viryl comes into contact with incompatible forms



Manufacturer







METHOD 1

METHOD 2

METHOD 3

X











[&]quot;This term and any comesponding data refer to typical performance in the specific test indicated and should not be construed to involve the bahavior of this or any other material under actual fire confisions.