

# Nassimi

PRODUCT SPECIFICATION SHEET



## Seine

### GENERAL SPECIFICATIONS

|                                       |   |   |                                     |
|---------------------------------------|---|---|-------------------------------------|
| Overall Composition                   | 94% Polyester / 4% TPU / 2% Silicone      |   |                                     |
| Backing Composition                   | TPU                                       |   |                                     |
| Stain Repellent                       | Silicone Based, PFAS-free                 |   |                                     |
| Weight                                | 19.7 oz. Per Linear Yard                  |   |                                     |
|                                       | 437 gsm                                   |   |                                     |
| Width                                 | 54"                                       |   |                                     |
| Direction                             | Up the Roll                               |   |                                     |
| Weave Construction                    | <input checked="" type="checkbox"/> Dobby | <input type="checkbox"/> Jacquard             | <input type="checkbox"/> Pile       |
| Dyeing Type                           | <input type="checkbox"/> Piece Dyed       | <input checked="" type="checkbox"/> Yarn Dyed | <input type="checkbox"/> Fiber Dyed |
| Fiber Composition (Synthetic/Natural) | 100% Synthetic Fiber                      |   |                                     |
| Fiber Type (Filament/Spun/Staple)     | 100% Staple                               |   |                                     |
| Staple Yarns Combed or Carded         | Carded                                    |   |                                     |
| High Tenacity Yarn                    | No  |   |                                     |
| Textured Yarn                         | Yes                                       |   |                                     |
| Yarns Per Inch                        | Warp: 17.0 EPI / Fill: 15.5 PPI           |   |                                     |
| Yarns Per Centimeter                  | Warp: 6.7 / Fill: 6.1                     |   |                                     |
| Yarn Size                             | Warp: T3.4N+T10S/2 / Fill: T3.4N          |   |                                     |
| Yarns Twisted 472 Turns+/Meter        | Yes                                       |   |                                     |

### PERFORMANCE SPECIFICATIONS

|                                       |                         |                           |
|---------------------------------------|-------------------------|---------------------------|
| Abrasion Resistance                   | 100,000+ Double Rubs*   | ASTM D4157-13(2022)       |
| Stain Resistance                      | Yes, PFAS-free          |                           |
| Bleach Resistance                     | Yes, 10% Dilution       |                           |
| Breaking Strength                     | Warp: 199 / Fill: 180   | ASTM D5034-21             |
| Brush Pill                            | Class 5.0               | ASTM D3511                |
| Colorfastness to Light                | Class 4.0 / 40 Hours    | AATCC 16.3, Opt. 3 - 2020 |
| Crocking Resistance                   | Dry: 4.5 / Wet: 5.0     | AATCC 8-2016              |
| Seam Slippage                         | Warp: 40.3 / Fill: 35.7 | ASTM D4034                |
| Tear Strength: Tongue Tear            | Warp: 33.2 / Fill: 37.1 | ASTM D2261-13(2017)       |
| Water Repellency Spray Test           | 100                     | AATCC 22-2017             |
| Water Resistance Hydrostatic Pressure | 270+ cm (maximum)       | AATCC 127-2017(2018)      |



\*ACT® Registered Certification Marks

\*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan

### FLAMMABILITY SPECIFICATIONS

|                      |      |
|----------------------|------|
| California TB 117:13 | Pass |
| UFAC Class I         | Pass |
| NFPA 260             | Pass |

## Seine

### GENERAL PRODUCT INFORMATION

|                   |                  |
|-------------------|------------------|
| Country of Origin | China            |
| HTS Code          | 5407.52.2060     |
| Roll Size         | 35-40 Yards/Roll |

### CLEANING CODE

Cleaning Code: SW, BC

For complete cleaning information, please refer to the Cleaning and Care Guide.

### SPECIAL HANDLING

Some types of adhesive tape may delaminate the backing off of Supreen fabric. It is recommended to use self-clinging stretch wrap instead of tape to secure the roll.

### REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

No added flame retardant chemicals – AB2998 compliant

No added anti-bacterial / anti-microbial chemicals

PFAS-free

Lead / heavy metal free

BPA free / tris free / formaldehyde free

Does not contain conflict minerals



*Disclaimer: This product meets the Healthy Interior goals of the Safer Chemical Challenge according to the manufacturer. Practice Greenhealth does not verify this information.*