

VIGOR



Specifications:

content: 100% Polyester
backing: Synthetic Latex Backing
finish: iClean
repeat: W 1.10" x H 0.47" RR
weight: 24.37 oz. / lin. yd.

width: 54 inches

Flammability Passes:

California Tech. Bulletin #117-2013
UFAC Class 1
NFPA 260 Class 1

Performance:

abrasion: Heavy Duty – 100,000 cycles
(Wyzenbeek – Cotton duck Abradant) (ASTM D4157)
light fastness: Class 4/40 hrs. min. (AATCC16A)
color fastness: Class 4 (ASTM D3597, AATCC 8) Wet
Class 4.5 (ASTM D3597, AATCC 8) Dry
physical properties: Class 4 (ASTM D3511) Brush Pill
215 lbs. warp, 148 lbs. weft (ASTM D5034) Breaking Strength
49 lbs. warp, 70 lbs. weft (ASTM D4034) Seam Slippage

made in: China

Care & Cleanability:

Cleaning code **W** - Spot clean only with water-based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam-to-seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm (www.iicrc.org).